

StratoForse

Start battery



Safe

Fire Resistant



2700Cycles

@50%DoD



FAST

Recharge



Temp.

Operation up to 80°C



60%

Lighter than lead-acid



0V

Recovery



Vibration Resistance

Improved



120000

Start-stop cycles

StratoForse Model	Capacity (Wh)	Voltage (V)	CCA (A)	Dimensions (mm) L * W * H (TH)	Weight (Kg)	Case Size
H4/LN1	198	12	360	207*175*190(190)	3.5	L1
L2-400L	240	12	450	242*175*190(190)	4.0	L2
NS40L	198	12	350	196*127*200(220)	3.5	NS40
NS60L	198	12	370	238*129*200(220)	3.7	NS60
NS60-Pro	240	12	420	238*129*200(220)	4.0	NS60
55D23L	240	12	450	232*173*200(220)	4.0	D23L
55D26L	240	12	450	260*173*200(220)	4.5	D26L
55D26R	240	12	450	260*173*200(220)	4.5	D26R
80D31R	312	12	520	306*173*200(220)	5.0	D31R
95D31L	396	12	650	306*173*200(220)	5.9	D31L
95D31R	396	12	550	306*173*200(220)	5.9	D31R
95D31R-Pro	594	12	800	306*173*200(220)	7.7	D31L

